



**THE DELTA™ II LINE
FEATURES A NEW
NO-TANGLE BACK PAD
WITH A STAND-UP
DORSAL D-RING FOR
EASIER AND QUICKER
CONNECTIONS !**

- The spring-loaded stand-up back D-ring* ensures fast, easy and safe connections.
- The exclusive Delta No-Tangle® design holds the shape of the harness for added comfort and ease of use - it greatly increases worker acceptance while reducing improper usage.
- Optional color coded quick-connect buckles make it easy to put on and fit every time.
- Add the optional Delta™ Comfort Pad for wrap-around comfort enhancing worker productivity and compliance. It's even removable and washable!
- Meets or exceeds all applicable industry standards including OSHA, the stringent ANSI Z359.1, EN361 and EN358.

i
SAFE™
INTELLIGENT
SAFETY SYSTEM
EQUIPPED

DBI-SALA harnesses have a reputation for quality, durability and excellent features! The recently **CE** certified Delta II harness range continues to build on this reputation with a host of new features.

Features include a unique back pad with a stand-up, spring-loaded back D-ring and optional patented DBI-SALA quick-connect buckles. Our exclusive Delta No-Tangle® Pad holds the shape of the harness, adds comfort and makes the harness easier to don. And every Delta™ harness combines maximum comfort, freedom of movement and ease of use. Each harness also incorporates special web keepers which tuck excess webbing neatly away.

Fast, Easy and Safe Connections. The Delta pad now incorporates a patented integrated spring-loaded "stand-up" dorsal D-ring. This provides the user with quick and safe connections enhancing ease of use and worker productivity.

Optional Quick-Connect Buckles easily adjust, engage and disengage with only one hand. These patented quick-connect buckles are also colour-coded, making it easy to don the harness correctly every time.

Wrap-Around Comfort. With the addition of the optional Delta™ Comfort Back Pad, your harness will be comfortable for longer hours of wear with less fatigue. It provides the comfort of a luxury harness at a midlevel harness price! The padding on the shoulders distributes the weight and keeps the pressure off, even when wearing heavy tool belts. Padding is removable and completely washable!

Specifications :

- **Webbing** - 45mm width, 100% Polyester, Minimum Breaking Strength >2600 daN
- **Optional Quick-Connect Buckles** - Minimum Breaking Strength >1700 daN, Heat-treated alloy steel, zinc plating with black e-coat finish on waist, chest, clear chromate finish on legs.
- **Thread** - High strength, 100% Polyester



Delta II Harness Models

KB11109117 : Single-point rear D-ring

Pass-Through Buckles :
 KB11109117=UNIV, KB11109118=SM, KB11109119=XL
 Quick-Connect Buckles :
 KB11110615=UNIV, KB11110616=SM, KB11110617=XL

KB11101288 : 2-point front + rear D-ring

Pass-Through Buckles :
 KB11101288=UNIV, KB11101289=SM, KB11101290=XL
 Quick-Connect Buckles :
 KB11101319=UNIV, KB11101320=SM, KB11101321=XL

KB11101294 : 2-point front + rear D-ring with work positioning belt (shown above)

Pass-Through Buckles :
 KB11101294=UNIV, KB11101295=SM, KB11101296=XL
 Quick-Connect Buckles :
 KB11101312=UNIV, KB11101313=SM, KB11101314=XL

- **D-rings** - Minimum Breaking Strength >2200 daN, Heat-treated forged alloy steel, yellow chromate zinc plating finish
- Meets or exceeds all applicable industry standards including OSHA, ANSI, the stringent ANSI Z359.1, and EN361 and EN358.