

# Datasheet

## Adjustable wrench, black - Kennedy

- Adjustable wrench with phosphate finish for improved strength and rigidity
- The jaws are heat-treated for extended tool life
- High polished corrosion-resistant finish
- 15° offset head angle for positive torque control
- Slimline tapered jaws for improved access into confined spaces
- Parallel jaws with smooth jaw adjustment and self-locking design prevents the jaws opening unintentionally even when under full load
- Suitable for industrial engineering, automotive agricultural, maintenance and assembly applications



| Article-number | Length |        | Jaw opening |         | Torque<br>kg/cm | Weight<br>gram |
|----------------|--------|--------|-------------|---------|-----------------|----------------|
|                | mm     | inches | mm          | inches  |                 |                |
| KEN5010040K    | 100    | 4"     | 17          | 21/32"  | 714             | 60             |
| KEN5010060K    | 150    | 6"     | 24          | 1"      | 1 670           | 140            |
| KEN5010080K    | 200    | 8"     | 28          | 1 3/32" | 3 100           | 260            |
| KEN5010100K    | 250    | 10"    | 33          | 1 5/16" | 5 190           | 400            |
| KEN5010120K    | 300    | 12"    | 38          | 1 3/8"  | 8 820           | 650            |
| KEN5010150K    | 375    | 15"    | 50          | 2"      | 17 295          | 1 040          |
| KEN5010180K    | 450    | 18"    | 60          | 2 3/8"  | 23 060          | 1 670          |
| KEN5010240K    | 600    | 24"    | 70          | 2 3/4"  | 25 000          | 3 300          |