

JALAS® 1878 OFFROAD

EN ISO 20345:2011, S3 SRC CI HRO HI

PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, boots/Ankle boots

NAIL PROTECTION MATERIAL Steel

FITTING Wide

SIZE RANGE (EU) 35-50

COLLECTION Gran Premio

PLATFORM Enduro

UPPER MATERIAL PU-coated leather

UPPER MATERIAL THICKNESS 1,6-1,8

PRONOSE MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Technical fleece

SOLE MATERIAL PU midsole, rubber outsole

INSOLE FX2 Pro

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®

FASTENING Laces, zipper

COLOUR Black, grey, yellow



SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
35	1878-35	6408487502071	47	1878-47	6408487440816
36	1878-36	6408487440700	48	1878-48	6408487440823
37	1878-37	6408487440717	49	1878-49	6408487502057
38	1878-38	6408487440724	50	1878-50	6408487502064
39	1878-39	6408487440731			
40	1878-40	6408487440748			
41	1878-41	6408487440755			
42	1878-42	6408487440762			
43	1878-43	6408487440779			
44	1878-44	6408487440786			
45	1878-45	6408487440793			
46	1878-46	6408487440809			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 1878 OFFROAD

FEATURES

ProNose toe reinforcement, wide fit, heat-resistant outsole, oil-resistant outsole, anti-static properties, bellows tongue, padded boot shaft, ventilating insole, pull loops, zipper, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, all-year use, environments with risk for outsole penetration, harsh environments



CE



Aluminium toecap



Ergothan Shock Absorption System



Nail protection in steel



Zipper



Heat-resistant outsole



Winter model



Water repellent



Anti-static properties



Oil-resistant outsole



ESD



ProNose toe reinforcement



Wide fit

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-05-25

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 1878 OFFROAD

COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-resistant upper

P: Penetration-resistant outsole

HRO: Heat-resistant outsole compound tested at 300°C

CI: Cold insulation

HI: Heat insulation

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 121-119: Orthopedic footwear adjustment according to German DGUV 121-119. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Nail protection in steel



Heat-resistant outsole



Water repellent



Oil-resistant outsole



ProNose toe reinforcement



Wide fit



Ergothon Shock Absorption System



Zipper



Winter model



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-05-25

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com