

Data sheet

metabo®

Angle grinder - Metabo WE 24-230 MVT, 110 Volt

- Metabo Marathon motor with patented dust protection for long service life
- Metabo safety switch prevents unintentional start
- Deadman's switch for high user protection
- Starting current limitation prevents the actuation of the lock on start-up
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly - for high user protection
- Electronic overload protection and restart protection
- LED signal indicates triggered restart protection or overheating
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Side handle can be mounted in three positions
- Rotating main handle: high safety and better handling when cutting
- Auto-stop carbon brushes to protect the motor
- Cable length 4 meter



Comes with:

- Guard
- Inner support flange
- Nut with two holes
- Side handle
- Flat-pin spanner

Article-number	Model	Voltage Volt	Rated input power Watt	No-load speed /min	Torque Nm	Grinding wheel mm	Revolution at rated load /min	Spindle thread	Weight kg
1398099	WE 24-230 MVT	110	2 300	6 600	17	230	4 600	M14	5,8*

*Weight without power cable



Vibration	
Surface grinding	4,8 m/s ²
Uncertainty of measurement K	1,5 m/s ²
Grinding with sandpaper	2,5 m/s ²
Uncertainty of measurement K	1,5 m/s ²
Noise emission	
Sound pressure level	94 dB(A)
Sound power level (LwA)	105 dB(A)
Uncertainty of measurement K	3 dB(A)