



**CRC PRO PAINT**  
Standard

Ref. : 10568-10577-10631-10632-10634

## 1. GENERAL DESCRIPTION

---

High quality lacquer for treated or untreated surfaces made out of metal, wood, ceramic, glass and a variety of plastics.

## 2. FEATURES

---

- Fast drying
- Excellent hiding power
- Long lasting gloss
- Good weathering and UV resistance
- Resists scratching and wear due to an increased hardness
- Good chemical and petroleum resistance

## 3. APPLICATIONS

---

Long term and esthetical protection of:

- Metal rims
- Wood
- Plastics

On the car, at home and for leisure equipment.

## 4. DIRECTIONS

---

- Remove old paint and scale and corrosion before application.
- Make sure the surface is clean and dry.
- For best results, surfaces must be sanded and treated with CRC Pro Paint Primer first.
- Assure the aerosol is at room temperature and shake for 2 minutes.
- Make a test on a separate or hidden part.
- Apply the lacquer in thin even cross layers from a distance of 25 to 30 cm.
- Shake the aerosol between each layer
- Clean the valve after use, by spraying upside down until only gas escapes.
- For extra protection and life time extension, the finished lacquer can be coated with CRC Pro Paint Varnish
- A safety data sheet (MSDS) according to EU directive 91/155/EEC and amendments is available for all CRC products.



Manufactured by :  
CRC Industries Europe BVBA  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
www.crcind.com





**CRC PRO PAINT**  
Standard

Ref. : 10568-10577-10631-10632-10634

**5. TYPICAL PRODUCT DATA (without propellant)**

---

Resin type	:	acrylic
Color	:	High gloss black Dull black High gloss white Silver
Temperature resistance	:	110°C
Covering	:	1,6 to 2,2 m <sup>2</sup> / 500 ml
Drying times (*)	to dust	: 5 – 10 minutes
	Stick free	: 10 – 20 minutes
	Cured / over paintable	: 2 hours

(\*) depending on coat weight, ventilation, temperature and relative humidity

**6. PACKAGING**

---

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com).

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10568-10577-10631-10632-10634 03 1105 01  
Date : 19 September 2013



Manufactured by :  
CRC Industries Europe BVBA  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)

