

Datasheet

Ring slogging wrench, inches - Kennedy

- Manufactured from forged and hardened steel
- With machine drive faces to ensure good contact with the fastener
- With flat striking faces to allow hammer blows to be used to loosen or tighten stubborn fasteners



Article-number	Size inches	Overall length mm	Weight kg
KEN5807500K	1 1/16"	180	0,4
KEN5807510K	1 1/8"	180	0,4
KEN5807520K	1 3/16"	190	0,5
KEN5807530K	1 1/4"	190	0,5
KEN5807540K	1 5/16"	190	0,5
KEN5807550K	1 3/8"	205	0,5
KEN5807560K	1 7/16"	205	0,5
KEN5807570K	1 1/2"	205	0,5
KEN5807580K	1 9/16"	230	0,8
KEN5807590K	1 5/8"	230	0,8
KEN5807600K	1 11/16"	230	0,8
KEN5807610K	1 3/4"	240	1,0
KEN5807620K	1 13/16"	240	1,0
KEN5807630K	1 7/8"	240	1,0
KEN5807640K	1 15/16"	225	1,1
KEN5807650K	2"	225	1,1
KEN5807660K	2 1/16"	225	1,1
KEN5807670K	2 1/8"	270	1,5
KEN5807680K	2 3/16"	270	1,5
KEN5807690K	2 1/4"	270	1,5
KEN5807700K	2 5/16"	280	1,8
KEN5807710K	2 3/8"	280	1,8
KEN5807720K	2 7/16"	280	1,8
KEN5807730K	2 1/2"	300	2,2
KEN5807740K	2 9/16"	300	2,2
KEN5807750K	2 5/8"	300	2,2
KEN5807760K	2 3/4"	330	3,3
KEN5807770K	2 13/16"	330	3,3
KEN5807780K	2 7/8"	330	3,3
KEN5807790K	2 15/16"	330	3,3
KEN5807800K	3"	330	3,3
KEN5807810K	3 1/8"	360	4,5
KEN5807820K	3 1/4"	360	4,5
KEN5807840K	3 1/2"	390	5,5
KEN5807850K	3 5/8"	420	5,3
KEN5807870K	3 7/8"	420	6,5
KEN5807900K	4 1/4"	450	8,0
KEN5807920K	4 5/8"	450	7,8